

H.265 Digital Video Recorder

TVI ■ AHD ■ CVI ■ CVBS ■ IP



HD CCTV
Over Coax



Introduction

VT-1400-HC series are 4 / 8 / 16 CH 1080P high definition DVRs with ability to connect analog and IP cameras simultaneously, which adopt the standard H.265 high profile compression format and the most advanced SOC technique to ensure real time recording in each channel and realize outstanding robustness of the system. TD-2100TS-HC support 4 / 8 / 16 CH video input, 1 / 1 CH audio input, simultaneous 4 / 8 / 16 CH playback. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.

Key Features

- 4 / 8 / 16 CH TVI / AHD video input, support 5MP/4MP/3MP/1080P/720P/WD1
- 4 / 8 / 16 CH CVI video input, support 4MP / 3MP/1080P / 720P/WD1
- 4 / 8 / 16 CH DVRs default support 2/4 / 8 CH IPC 5MP/4MP / 3MP / 1080P / 960P / 720P
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate. Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timer / motion
- Playback : 4 / 8 / 16 CH simultaneously playback
- Search: time slice, time, event (manual, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log review and device status review
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Android OS

Specification		VT-1404HC	VT-1408HC	VT-1416HC
System	Compression	Standard H.265 High Profile		
	CPU	Cortex A9		
	OS	Embedded Linux		
Video	Input	BNC x 4	BNC x 8	BNC x 16
	Resolution	TVI/AHD : 5MP/4MP/3MP/1080P/720P/WD1 CVI : 4MP/3MP/1080P/720P/WD1		
	IP Input / Access Bandwidth	2CH (Up to 6CH)	4CH (Up to 12CH)	8CH (Up to 16CH)
	Output	HDMI x 1 : 1920 x 1080 / 1280 x 1024 / 1024 x 768 VGA x 1 : 1920 x 1080 / 1280 x 1024 / 1024 x 768 BNC x 1 : CVBS (used as the main or spot output)		
Audio	Input	RCA x 1		
	Output	RCA x 1		
	Two-way audio	Take up channel one audio input		
Record	Resolution	5MP Lite/4MP Lite/1080P/1080P Lite/720P/WD1		
	Frame Rate	5MP Lite : 10fps 4MP Lite : 12fps (PAL)/15fps (NTSC) 1080P : 12fps (PAL)/15fps (NTSC) 1080P Lite/720P/WD1 : 25fps (PAL)/30fps (NTSC)		
	Bit Rate	32Kbps ~ 4Mbps	32Kbps ~ 4Mbps	32Kbps ~ 5Mbps
	Mode	Manual, timer, motion		
IP Input	Resolution	Up to 5MP@25fps	Up to 5MP@30fps	Up to 5MP@30fps
	Playback	4 CH	8 CH	16 CH
Playback	Search	Time slice / time / event / tag search		
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events		
	Function	Play, pause, FF, FB, digital zoom, etc.		
Alarm	Mode	Manual, motion, exception		
	Input	No		
	Output	No		
	Triggering	Record, snap, preset, e-mail, etc.		
Network	Interface	RJ45 10/100Mbps x 1		
	Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP		
	Web Client	Multiple users online		
Mobile Device	OS	iOS, Android		
	Storage	HDD	SATA x 1, max. 6 T	SATA x 1, max. 6 T SATA x 1, max. 8 T
Backup	Local Backup	U disk, USB removable HDD		
	Network Backup	Yes		
Port	RS485	RS485 x 1, connect to PTZ or keyboard		
	USB	USB 2.0 x 2 (one in the front panel and the other in the rear panel)		
	Remote Cont.	Optional (Remote Controller)		
Others	Power Supply	DC12V / 1.5A	DC12V / 2A	DC12V / 3A
	Consumption	≤ 5W (without HDD)	≤ 8W (without HDD)	≤ 10W (without HDD)
	Dimensions	255 x 233 x 42 (W x D x H) mm		
	Work Temp.	Work Environment -10 ~ 50°C, 10% ~ 90% humidity		

Design and specifications are subject to change without notice.

Dimensions

