

HWT-T120-P
2 MP Indoor Fixed Turret Camera



- 1080p turret camera
- Smart IR: up to 20 m IR distance
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification





Interface	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
Selection Parameter	
Case Type	Turret
Length Type	Fixed Lens
IR Distance	<30m
WDR	DWDR
Star Light	N/A
Power Supply	DC12V
Protection Level	N/A
Video Output	4 in 1
Resolution	2MP
Menu	
AGC	High/Medium/Low/Off
Day/Night Mode	Auto/Color/BW (Black and White)
Backlight Compensation	Support
DWDR (Digital Wide Dynamic Range)	Support
Language	English
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
Camera	
Image Sensor	2 MP CMOS image sensor
Signal System	PAL/NTSC
Frame Rate	PAL: 1080p@25fps,NTSC: 1080p@30fps
Min. illumination	0.01 Lux@(F2.0, AGC ON), 0 Lux with IR
Shutter Time	1/25 (1/30) s to 1/50,000 s
Lens	2.8 mm, 3.6 mm, 6 mm
Horizontal Field of View	103° (2.8 mm), 80.7° (3.6 mm), 50.1° (6 mm)
Lens Mount	M12
Day & Night	IR cut filter
Synchronization	Internal synchronization
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Effective Pixels	1920 (H) × 1080 (V)
General	
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±15%
Power Consumption	Max. 4 W
Material	Plastic
IR Range	Up to 20 m
Dimensions	∅ 85.4 mm × 76.12 mm (∅ 3.38" × 2.67")
Weight	130 g (0.29 lb.)

▪ **Available Model**

HWT-T120-P

▪ **Accessory**

▪ **Optional**

DS-1272ZJ-110-TRS Wall Mount	DS-1275ZJ-SUS Vertical Pole Mount	DS-1276ZJ-SUS Corner Mount	DS-1280ZJ-XS Junction Box
			

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq