

DS-3E1318P-EI/M 16-Port 10/100M PoE




- 16 × 10/100 Mbps PoE port, 1 × Gigabit combo, 1 × Gigabit RJ45 port.
- IEEE 802.3at/af standard for PoE ports.
- Network topology management, alarm push, network health monitor.
- 6 KV surge protection for PoE ports.
- AF/AT camera can reach up to 300 m in extend mode.

▪ Specification

Model		DS-3E1318P-EI/M
Network Parameters	Port Type	RJ45 port,full duplex,MDIMDI-X adaptive
	Standard	IEEE 802.3,IEEE 802.3u,IEEE 802.3x,IEEE 802.3ab,IEEE 802.3z
	Ports	16 × 10/100 Mbps PoE port,1 × Gigabit combo,1 × Gigabit RJ45 port
	High Priority Ports	Ports 1 to 8
	Forwarding Mode	Store-and-forward switching
	Working Mode	Standard mode (default),Extend mode
	MAC Address Table	16 K
	Switching Capacity	7.2 Gbps
	Packet Forwarding Rate	5.36 Mpps
	Internal Cache	4 Mbits
PoE Power Supply	PoE Standard	IEEE 802.3af,IEEE 802.3at
	PoE Power Pin	End-span: 1/2(-), 3/6(+) Mid-span: 4/5(+), 7/8(-) 8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
	PoE Port	PoE: Ports 1 to 16
	Max. Port Power	30 W
	PoE Power Budget	130 W
Software Function	Device Maintenance	Support remote upgrade, default parameter restoration, logs viewing, basic network parameter configuration, import and export configuration, and time synchronization.
General	Shell	Metal material
	Net Weight	1.8 kg (4.0 lb)
	Gross Weight	3.0 kg (6.6 lb)
	Dimensions (W × H × D)	335.00 mm × 44.50 mm × 226.00 mm (13.19" × 1.75" × 8.90")
	Operating Temperature	0 °C to 45 °C (32 °F to 113 °F)
	Storage Temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operating Humidity	5% to 95% (no condensation)
	Relative Humidity	5% to 95% (no condensation)
	Power Supply	100-240 VAC, 50/60 Hz, Max. 2.5 A
	Max. Power Consumption	150 W
Approval	EMC	CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010 +A1: 2015); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016)
	Safety	UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013)
	Chemistry	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No.1907/2006)

▪ Typical Application



▪ Available Model

DS-3E1318P-EI/M

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq