

UV-IPC2122LB-AF28WK-G

2 MP WiFi IP Camera

Easy range

1/2.9" Progressive Scan CMOS

2.8 mm Lens

IR LEDs Range 30 m

WEB, CMS, Smartphone and NVR
interface



Uniview

IP camera

Easy range

1/2.9" Progressive Scan CMOS

2 Megapixel (1920x1080)

2.8 mm Lens

0 Lux

IR Range 30 m

Compression Ultra265/H.265/H.264

RJ-45 10/100 BaseT

Wifi IEEE802.11b/g/n

Weatherproof IP67

IR Cut

Built-in microphone

WDR 120dB

MicroSD 128GB

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

Specifications

| | |
|----------------------|---|
| Brand | Uniview |
| Range | Easy |
| Image sensor | 1/2.9" Progressive Scan CMOS |
| Maximum resolution | 2 Megapixel (1920x1080) |
| Main Stream rate | 1080P (1920*1080)@30fps; 720P (1280*720)@30fps; |
| Extra Stream rate | 720P (1280*720)@30fps; D1 (720*576)@30fps; 640*360@30fps; 2CIF(704*288)@ 30fps; CIF(352*288)@30fps; |
| Compression | Ultra265/H.265/H.264 |
| Lens | 2.8 mm |
| Minimum illumination | 0.01 Lux (Colour) |
| Infrared range | 30 m |
| Image improvements | DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask |
| Day / Night | Mechanical ICR filter |
| Internal memory | MicroSD card, Max 128 GB |
| Alarms | No |
| Audio | Built-in microphone |
| Network interface | IEEE802.11b/g/n |
| Remote access | Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive) |
| Interoperability | ONVIF |
| Power | DC 12V / 4W |
| Temp. operation | -30° C ~ 60° C |
| Degree of protection | Weatherproof IP67 |
| Dimensions | 172 (H) x 76 (W) x 72 (D) mm |
| Weight | 250 g |