

W15-Pro

AX3000 Wi-Fi 6 Wireless In-Wall Access Point

Hardware	
Dimension	86*86*32mm
Interfaces	1*10/100/1000 Mbps PoE+Data Input LAN 1*10/100/1000 Mbps Output LAN
Button	1*Reset
Antenna	4dBi+5dBi
Maximum Power Consumption	8.5W
LED Indicator	1*SYS
Power Supply	PoE 802.3af
Wireless	
Frequency Range	2.4GHz & 5GHz dual band
Maximum wireless speed	2.4GHz:574Mbps 5GHz:2402Mbps
Standard&Protocol	IEEE 802.11b/g/n/ac/ax(wave2)
Reception Sensitivity	2.4GHz 802.11b -95.5dBm 2.4GHz 802.11n (MCS7) -72.5dBm 5GHz 802.11a -97.5dBm 5GHz 802.11n (MCS7) -77.5dBm
Software	
MU-MIMO	Support
Operating Mode	AP/Client+AP
Max. No. of SSID	2.4GHz: 8 5GHz: 8
Hide SSID	Support

WEP	Support
WPA-PSK	Support
WPA2-PSK	Support
WPA	Support
WPA2	Support
Access control	Support
Adjustable power transmit	Support
AP isolation	Support
Connected clients control	Support
RSSI Threshold	Support
WMM	Support
VLAN tagging for SSID	Support
LED control	Support
Diagnostics	Support
Schedule Reboot	Support
Reboot at specified interval	Support
System Logs	Support
Firmware upgrade	Support
Reboot	Support
Reset Button	Support

Backup configuration	Support
Restore configuration	Support
Centralized Management	M3 or Tenda Router with AP Controller feature
Others	
Operation Temperature	-10°C ~ 40°C
Storage Temperature	-30°C ~ 70°C
Operating Humidity	10%~90% non-condensing
Storage Humidity	5%~90% non-condensing
Default login IP	192.168.0.254
Certification	CE/RoHS