Picture     Argus Series B330       Model     Argus Series B330       Image Sensor     1/2.7°CMOS sensor       Resolution     2880 x 1616 (5 megapixels) @15fps       Video Compression     H-265       Field of View     Vertical: 55°       Field of View     Up to 10 meters (351); LEC: 6pcs/0.8w/850nm (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/6500k       Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Sub stream: 10fps - 15fps (default: 3072kbp       Code Rate     Sub stream: 10fps - 15fps (default: 3072kbp)       Code Rate     Sub stream: 10fps - 15fps (default: 3072kbp)       Code Rate     Sub stream: 10fps - 15fps (default: 3072kbp)       Code Rate     Sub stream: 10fps - 15fps (default: 3072kbp)       Code Rate     Sub stream: 10fps - 15fps (default: 3072kbp)       Code Rate     Sub stream: 10fps - 15fps (default: 13072kbp)       Code Rate     Sub stream: 10fps - 15fps (default: 13072kbp)       Code Rate     Supports Max 128GB microSD card       Requirements     Power Port     USB Type-C port       Interface     Power Port     USB Type-C port	Ceplink Reolink Innovation Limited			
Video & Audio     Image Sensor     1/2.7°CMOS sensor       Video Compression     2880 x 1616 (5 megapixels) @15fps       Video Compression     H.255       Field of View     Vertical: 55°       Diagonal: 125°     Diagonal: 125°       Color Night Vision     Up to 10 meters (33ft); LED: 6pcs/0.8w/850nm (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/6500k       Frame Rate     Sub stream: 101ps - 15fps (default: 15fps)       Code Rate     Main stream: 102s - 15fps (default: 15fps)       Code Rate     Sub stream: 102s - 4096k/bps (default: 3072k/bp       Audio     Two-way audio       Power     Battery       Sub stream: 102s - 15fps (default: 672K/bps)       Audio In/Out     Sub ports Max.128GB microSD card       Interface     Power Port     USB Type-C port       Audio In/Out     Built-in microphone and speaker       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4CHz/SCHz       Viseless Security     WPA/WPA2       Software     Smart Alarm     PiR detection; person detection; whicle detection; person detection; vehicle detection; persondetection; vehicle detection; person detection; vehi	Picture			
Resolution     2880 x 1616 (5 megapixels) @15fps       Video Compression     H-265       Video Compression     Horizontal: 105°       Field of View     Vertical: 55°       Diagonal: 125°     Infrared Night Vision       Infrared Night Vision     Up to 10 meters (33ft): LED: 6pcs/0.8w/850nm (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/8500k       Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Main stream: 10fps - 15fps (default: 3072kbps)       Sub stream: 104xkbps - 4096kbps (default: 3072kbp     Sub stream: 104xkbps - 4096kbps (default: 3072kbps)       Power     Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Power Port     USB Type-C port       Interface     SD Card Slot     Supports Max. 128GB microSD card       Wi-Fi     Operating Frequency     2.4CH2/5CHz       Wireless Standard     IEEE 802.11 a/b/g/n       Wireless Standards     SSL, TCP/IP, UDP, UNP, SMTP, NTP, P2P       User Access     Max.12 simultaneous streams (2 main & 10 sub stream       PIR Detecting Angle     To 10° chorizontal       PIR Detecting Angle     Tingered recording	Model	Argus Series B330		
Video Compression     Horizontal: 105 °       Video Compression     Horizontal: 105°       Field of View     Vertical: 55°       Diagonal: 125°     Diagonal: 125°       Video & Audio     Infrared Night Vision     Up to 10 meters (33ft); LED: 6pcg/08//850nm (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/6500k       Frame Rate     Main stream: 10fps - 15fps (default: 15fps)       Code Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Sub stream: 10fps - 15fps (default: 072Kbps)       Audio     Two-way audio       Power     Battery       Sub stream: 104xbps - 4096kbps (default: 672Kbps)       Audio     Two-way audio       Power Port     USB Type-C port       SD Card Slot     Supports Max. 128GB microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wireless Standard     IEEE 80211 a/b/g/n       Operating Frequency     2.4GH2/SCH2       Wireless Standards     SSL, TCP/IP, UDP, UDPN, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream       PIR Detecting Angle </th <th rowspan="14">Video &amp; Audio</th> <th>Image Sensor</th> <th>1/2.7"CMOS sensor</th>	Video & Audio	Image Sensor	1/2.7"CMOS sensor	
Video & Audio     Horizontal: 105°       Video & Audio     Infrared Night Vision     Up to 10 meters (33ft); LED: 6pcs/0.8w/850nm (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/8500k       Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Main stream: 10fps - 15fps (default: 3072Kbps)       Code Rate     Sub stream: 04Kbps - 4096Kbps (default: 3072Kbps)       Audio     Two-way audio       Power     Battery       Battery     6000mAh rechargeable battery (Battery Ifle varies based settings, usage & temperature.)       Power Port     USB Type-C port       SD Card Slot     Supports Max.128GB microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4GH2/SGH2       Vireless Standards     SSL_TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max.12 simultaneous streams (2 main & 10 sub stream       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       PIR Detecting Angle     Niz simultaneous streams (2 main & 10 sub stream <td>Resolution</td> <td>2880 x 1616 (5 megapixels) @15fps</td>		Resolution	2880 x 1616 (5 megapixels) @15fps	
Video & Audio     Field of View     Vertical: 55°       Video & Audio     Infrared Night Vision     Up to 10 meters (33ft); LED: 6pcs/0.8w/850nm (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/6500k       Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Main stream: 1024kbps - 4096kbps (default: 5072kbps)       Audio     Two-way audio       Power     Battery       Requirements     SD Card Slot       SD Card Slot     Supports Max. 128GB microSD card       Interface     Wireless Standard       Wireless Standard     IEEE 80211 a/b/g/n       Wireless Standard     SSL, TCP/IP, UDP, UNP, SMTP, NTP, P2P       Software     Smart Alarm       Picocls & Standards     SSL, TCP/IP, UDP, UNP, SMTP, NTP, P2P       User Access     Max.12 simultaneous streams (2 main & 10 sub stream: detection; person detection; vehicle detection; person detection; vehicle detection; person detection; vehicle detection; person detection; Parson detection		Video Compression	H.265	
Video & Audio     Infrared Night Vision     Up to 10 meters (35ft); LED: 6pcs/0.8w/850nm (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/6500k       Frame Rate     Main stream: 10fps - 15fps (default: 15fps)       Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Main stream: 1024Kbps - 4096Kbps (default: 5072Kbp)       Audio     Two-way audio       Power     Battery       Requirements     5D Card Slot       Power Requirements     SD Card Slot       SD Card Slot     Supports Max.128CB microSD card       Reset Button     VES       Audio In/Out     Built-in microphone and speaker       Wireless Standard     IEEE 802.11 a/b/g/n       Wireless Security     WPA/WPA2       OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max.12 simultaneous streams (2 main & 10 sub stream: detection; prison detection; whicle detection; prison detection; whicle detection; prison detection; PIR Detecting Distance       Adjustable up to 10m (33ft)     PIR Detecting Angle       100° horizontal     Recording Modes       Recordin		Field of View	Horizontal: 105°	
Video & Audio     Infrared Night Vision     Up to 10 meters (33't): LED: 6pcs/0.8w/850nm (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/6500k       Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Sub stream: 107ps - 15fps (default: 15fps)       Audio     Wain stream: 1024kbps - 4096kbps (default: 3072kbp)       Audio     Two-way audio       Power     Battery       Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Power Port     USB Type-C port       SD Card Slot     Supports Max. 1286B microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wireless Standard     IEEE 802.11 a/bg/n       Wireless Standard     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream: detection       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream: detection       PIR Detecting Distance     Adjustable up to 100 (33't)       PIR Detecting Angle     100° horizontal       Recordin			Vertical: 55°	
Video & Audio     Infrared Night Vision     (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/6500k       Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Sub stream: 1024kbps - 4096kbps (default: 3072kbp)       Audio     Two-way audio       Power     Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Interface     SD Card Slot     Supports Max. 128CB microSD card       Reset Button     YES     Audio IEEE 802.11 a/b/g/n       Wi-Fi     Operating Frequency     2.4CH2/SCH2       Wireless Standard     IEEE 802.11 a/b/g/n       Vireless Standard     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream: detection, whicle detection, production (33ft)       PIR Detecting Angle     IO0° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant, Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie detection, P65       Mireless Security     YES       Smart Alarm     PIR detec			Diagonal: 125°	
Video & Audio     Infrared Night Vision     (Auto-switching with IR-cut filter)       Color Night Vision     With spotlights: 2pcs/2w/6500k       Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Sub stream: 1024kbps - 4096kbps (default: 3072kbp)       Audio     Two-way audio       Power     Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Interface     SD Card Slot     Supports Max. 128CB microSD card       Reset Button     YES     Audio IEEE 802.11 a/b/g/n       Wi-Fi     Operating Frequency     2.4CH2/SCH2       Wireless Standard     IEEE 802.11 a/b/g/n       Vireless Standard     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream: detection, whicle detection, production (33ft)       PIR Detecting Angle     IO0° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant, Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie detection, P65       Mireless Security     YES       Smart Alarm     PIR detec		Infrared Night Vision	Up to 10 meters (33ft): LED: 6pcs/0.8w/850nm	
Frame Rate     Main stream: 10fps - 15fps (default: 15fps)       Sub stream: 10fps - 15fps (default: 15fps)     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Main stream: 1024Kbps - 4096Kbps (default: 3072Kbps)       Audio     Two-way audio       Power     Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Interface     Power Port     USB Type-C port       SD Card Slot     Supports Max. 128GB microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4GHz/SGHz       Vireless Security     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream: detection; person detection; vehicle detection; person detection       PIR Detecting Angle     100° horizontal       PIR Detecting Angle     100° horizontal       PIR Detecting Angle     Cloud Storage       Smart Alarm     Geogle Assistant; Alxea				
Frame Rate     Main stream: 10fps - 15fps (default: 15fps)       Sub stream: 10fps - 15fps (default: 15fps)     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Main stream: 1024Kbps - 4096Kbps (default: 3072Kbps)       Audio     Two-way audio       Power     Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Interface     Power Port     USB Type-C port       SD Card Slot     Supports Max. 128GB microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4GHz/SGHz       Vireless Security     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream: detection; person detection; vehicle detection; person detection       PIR Detecting Angle     100° horizontal       PIR Detecting Angle     100° horizontal       PIR Detecting Angle     Cloud Storage       Smart Alarm     Geogle Assistant; Alxea		Color Night Vision		
Frame Rate     Sub stream: 10fps - 15fps (default: 15fps)       Code Rate     Main stream: 1024Kbps - 4096Kbps (default: 3072Kbp)       Audio     Two-way audio       Power     Battery       Requirements     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Interface     SD Card Slot       Sub stream: 10/ps - 15fps (default: 3072Kbp)       Mine State S				
Code Rate     Main stream: 1024Kbps - 4096Kbps (default: 3072Kbp)       Sub stream: 64Kbps - 672Kbps (default: 3072Kbps)     Sub stream: 64Kbps - 672Kbps (default: 3072Kbps)       Power     Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Interface     Power Port     USB Type-C port       SD Card Slot     Supports Max. 128GB microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wi-Fi     Operating Frequency     2.4CHz/SCHz       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4CHz/SCHz       Wireless Standard     SSL, TCP/IP, UDP, UDPN, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream       Software     Smart Alarm     PIR detection; person detection; vehicle detection; person detection; vehicle detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)     PIR Detecting Angle       Time Lapse     YES     Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie     Cloud Storage       Working     Operating Temperature				
Code Rate     Sub stream: 64Kbps - 672Kbps (default: 672Kbps)       Audio     Two-way audio       Power     Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Interface     Power Port     USB Type-C port       SD Card Slot     Supports Max. 128GB microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wi-Fi     Operating Frequency     2.4GHz/SGHz       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4GHz/SGHz       Wireless Security     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrid <t< td=""><td rowspan="2">Code Rate</td><td></td></t<>		Code Rate		
Audio     Two-way audio       Power     Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Interface     Power Port     USB Type-C port       SD Card Slot     Supports Max.128GB microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4GHz/SGHz       Wireless Security     WPA/WPA2       OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Software     Smart Alarm     PIR detection; person detection; person detection; person detection; person detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity				
Power Requirements     Battery     6000mAh rechargeable battery (Battery life varies based settings, usage & temperature.)       Interface     Power Port     USB Type-C port       SD Card Slot     Supports Max. 128CB microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wi-Fi     Operating Frequency     2.4GHz/SGHz       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4GHz/SGHz       Wireless Security     WPA/WPA2       OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C++55°C (14°F+131°F)       Operating Temperature     -10°C++55°C (14°F+131°F)		Audio		
RequirementsBatterysettings, usage & temperature.)InterfacePower PortUSB Type-C portSD Card SlotSupports Max. 128GB microSD cardReset ButtonYESAudio In/OutBuilt-in microphone and speakerWi-FiOperating FrequencyOperating Frequency2.4GHz/SGHzWireless SecurityWPA/WPA2SoftwareOS SupportedProtocols & StandardsSSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2PUser AccessMax. 12 simultaneous streams (2 main & 10 sub stream detection)PIR Detecting DistanceAdjustable up to 10m (33ft)PIR Detecting Angle100° horizontalRecording ModesTriggered recordingTime LapseYESSmart Home CompatibilityGoogle Assistant; AlxeaCloud StorageSupports Reolink Cloud (available in selected countrie Operating HumidityWorking EnvironmentOperating TemperatureOperating Humidity20% ~ 85%WeatherproofIP65Dimensions127 x 90 x 56mm	Power	Addio		
Interface     Power Port     USB Type-C port       SD Card Slot     Supports Max. 128GB microSD card     Reset Button     YES       Audio In/Out     Built-in microphone and speaker     Wireless Standard     IEEE 802.11 a/b/g/n       Wi-Fi     Operating Frequency     2.4GHz/SGHz     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UDPN, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream detection; person detection; vehicle detection; person detection; vehicle detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Temperature     -10°C~+55°C       Operating Temperature     -10°C~+55°C       Operating Temperature     -10°C~+55°C       Operating Temperature     -10°C~+55°C       Operating Temperature     -10°C~+55°C <td></td> <td>Battery</td> <td></td>		Battery		
Interface     SD Card Slot     Supports Max.128GB microSD card       Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wi-Fi     Operating Frequency     2.4GHz/SGHz       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4GHz/SGHz       Wireless Security     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max.12 simultaneous streams (2 main & 10 sub stream detection; person detection; vehicle detection; person detection; Vehicle detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65		Power Port		
Interface     Reset Button     YES       Audio In/Out     Built-in microphone and speaker       Wi-Fi     Operating Frequency     2.4GHz/5GHz       Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4GHz/5GHz       Wireless Security     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UDNP, SMTP, NTP, P2P       User Access     Max.12 simultaneous streams (2 main & 10 sub stream detection; person detection; vehicle detection; person detection; vehicle detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm		SD Card Slot		
Audio In/Out     Built-in microphone and speaker       Wi-Fi     Wireless Standard     IEEE 802.11 a/b/g/n       Operating Frequency     2.4GHz/5GHz       Wireless Security     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm		Reset Button		
Wireless Standard     IEEE 802.11 a/b/g/n       Wireless Standard     Operating Frequency     2.4GHz/5GHz       Wireless Security     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream detection; vehicle detection; person detection; vehicle detection; person detection       Other Features     Smart Alarm     PIR detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm			Built-in microphone and speaker	
Wi-Fi     Operating Frequency     2.4GHz/5GHz       Wireless Security     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream detection; person detection; vehicle detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie -10°C++55°C (14°F+131°F)       Operating Temperature     -10°C+55°C (14°F+131°F)       Operating Temperature     -10°C + 55°C (14°F+131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm	Wi-Fi			
Wireless Security     WPA/WPA2       Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream       PIR Detecting Distance     PIR detection; person detection; vehicle detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countried			¥	
Software     OS Supported     PC: Windows, Mac OS; Smartphone: iOS, Android       Software     Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream       PIR Detecting Distance     PIR detection; person detection; vehicle detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Working     Dimensions       Environment     Dimensions				
Software     Protocols & Standards     SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P       User Access     Max. 12 simultaneous streams (2 main & 10 sub stream detection; vehicle detection; person detection; vehicle detection; person detection; vehicle detection; person detection       Other Features     Smart Alarm     PIR detection; person detection; vehicle detection; person detection; vehicle detection; person detection       Other Features     PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Orbit Features     Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countried)       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm	Software		, 	
User Access     Max. 12 simultaneous streams (2 main & 10 sub stream       Smart Alarm     PIR detection; person detection; vehicle detection; person detection       PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm			· · · · · · · · · · · · · · · · · · ·	
Smart Alarm     PIR detection; person detection; vehicle detection; person detection; vehicle detection; person detection; vehicle detection; person detection       Other Features     PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm				
Smart Alarm     detection       Other Features     PIR Detecting Distance     Adjustable up to 10m (33ft)       PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countried countried)       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm	Other Features	0361 ACC633	· · · · · · · · · · · · · · · · · · ·	
Other Features     PIR Detecting Distance     Adjustable up to 10m (33ft)       Other Features     PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countries       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm		Smart Alarm		
Other Features     PIR Detecting Angle     100° horizontal       Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countries       Working     Operating Temperature       Invironment     Operating Humidity       Weatherproof     IP65       Dimensions     127 x 90 x 56mm		PIR Detecting Distance		
Other Features     Recording Modes     Triggered recording       Time Lapse     YES       Smart Home Compatibility     Google Assistant; Alxea       Cloud Storage     Supports Reolink Cloud (available in selected countrie       Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm			100° horizontal	
Time Lapse YES   Smart Home Compatibility Google Assistant; Alxea   Cloud Storage Supports Reolink Cloud (available in selected countrie   Operating Temperature -10°C~+55°C (14°F~131°F)   Operating Humidity 20% ~ 85%   Weatherproof IP65   Dimensions 127 x 90 x 56mm			Triggered recording	
Smart Home Compatibility Google Assistant; Alxea   Smart Home Compatibility Google Assistant; Alxea   Cloud Storage Supports Reolink Cloud (available in selected countries   Working Operating Temperature   Operating Humidity 20% ~ 85%   Weatherproof IP65   Dimensions 127 x 90 x 56mm				
Working Environment Operating Temperature -10°C~+55°C (14°F~131°F)   Weatherproof IP65   Dimensions 127 x 90 x 56mm				
Working Environment     Operating Temperature     -10°C~+55°C (14°F~131°F)       Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm				
Working Environment     Operating Humidity     20% ~ 85%       Weatherproof     IP65       Dimensions     127 x 90 x 56mm		¥		
Environment Weatherproof IP65 Dimensions 127 x 90 x 56mm	-			
Dimensions 127 x 90 x 56mm	Environment			
Machanical 127 X 30 X 301111	Mechanical			
Weight (Battery Included) 330g				
2-year limited warranty. For support, visit				
Warranty     Limited Warranty     2-year limited warranty. For support, visit       https://support.reolink.com/hc/en-us/.     https://support.reolink.com/hc/en-us/.	Warranty	Limited Warranty		