



Reolink Innovation Limited

<b>Picture</b>			
<b>Model</b>	<b>Argus Series B350</b>		
<b>Video &amp; Audio</b>	Image Sensor	1/2.7" CMOS sensor	
	Resolution	3840 x 2160 (8 megapixels) @15fps	
	Video Compression	H.265	
	Field of View	Horizontal:	105°
		Vertical:	55°
		Diagonal:	125°
	Infrared Night Vision	Up to 10 meters (33ft); LED: 6pcs/0.8w/850nm (Auto-switching with IR-cut filter)	
	Color Night Vision	With spotlights: 2pcs/2w/6500k	
	Frame Rate	Main stream:	10fps - 15fps (default: 15fps)
Sub stream:		10fps - 15fps (default: 15fps)	
Code Rate	Main stream:	1024Kbps - 4096Kbps (default: 3072Kbps)	
	Sub stream:	64Kbps - 672Kbps (default: 672Kbps)	
Audio	Two-way audio		
<b>Power Requirements</b>	Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)	
<b>Interface</b>	Power Port	USB Type-C port	
	SD Card Slot	Supports Max. 128GB microSD card	
	Reset Button	YES	
	Audio In/Out	Built-in microphone and speaker	
<b>Wi-Fi</b>	Wireless Standard	IEEE 802.11a/b/g/n	
	Operating Frequency	2.4GHz/5GHz	
	Wireless Security	WPA/WPA2	
<b>Software</b>	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P	
	User Access	Max. 12 simultaneous streams (2 main & 10 sub streams)	
<b>Other Features</b>	Smart Alarm	PIR detection; motion detection; person detection; vehicle detection; pet detection	
	PIR Detecting Distance	Adjustable up to 10m (33ft)	
	PIR Detecting Angle	100° horizontal	
	Recording Modes	Triggered recording	
	Time Lapse	YES	
	Smart Home Compatibility	Google Assistant; Alexa	
	Cloud Storage	Supports Reolink Cloud (available in selected countries)	
<b>Working Environment</b>	Operating Temperature	-10°C~+55°C (14°F~131°F)	
	Operating Humidity	20% ~ 85%	
	Weatherproof	IP65	
<b>Mechanical</b>	Dimensions	127 x 90 x 56mm	
	Weight (Battery Included)	335g	
<b>Warranty</b>	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> .	