



Reolink Innovation Limited

Picture		
Model	E Series E330	
Video & Audio	Image Sensor	1/2.7" CMOS Sensor
	Video Resolution	2560x1440 (4MP)@15FPS
	Lens	f=4mm, F=2.0
	Video Format	H.264
	Field of View	Horizontal: 84°
		Vertical: 45°
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 12 Meters (40ft)(LED: 8pcs/14mil/850nm)
Audio	Two-way Audio	
Power	DC Power	DC 5V=1A
Interface	Power	DC power port
	System	Reset Button
	Ethernet	One 10M/100Mbps RJ45
	Storage	MicroSD card slot (Max. 256GB)
	Audio	Built-in Microphone and Speaker
Pan&Tilt	Pan &Tilt Range	Pan: 355°, Tilt: 0°~50°
	Auto Tracking	Support
Wi-Fi	Wireless Standard	IEEE 802.11 a/b/g/n
	Operating Frequency	2.4 GHz/5 GHz
	Wireless Security	WPA-PSK/WPA2-PSK
Software Features	Frame Rate	Main Stream: 2fps - 25fps(default: 15fps)
		Sub Stream: 4fps - 15fps(default: 7fps)
	Code Rate	Main Stream: 1024Kbps -5120Kbps(default: 3072Kbps)
		Sub Stream: 128Kbps -512Kbps(default: 160Kbps)
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/Human Detection/Pet Detection
	Record Mode	Motion Record/Schedule Record (Default: Motion Record)
	Protocols & Standards	SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, P2P
Maximal User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams); 20 Users (1 admin account & 19 user accounts)	
Working Environment	Work with	Google Assistant, Reolink NVR
	Temperature	Operating Temperature: -10°C~+55°C (14°F~131°F)
Size & Weight	Humidity	Operating Humidity: 20% ~ 85%
	Dimension	Φ84x118mm
Warranty	Weight	235g
	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/