




Reolink Innovation Limited

Picture		
Model	Go Series G330	
Video & Audio	Image Sensor	1/2.7" CMOS sensor
	Resolution	2560 x 1440 (4MP) @15FPS
	Video Compression	H.265
	Field of View	Horizontal: 105°
		Vertical: 55°
		Diagonal: 125°
	Infrared Night Vision	Up to 10 meters (33ft); LED: 6pcs/14mil/850nm (Auto-switching with IR-cut filter)
	Frame Rate	Main stream: 10fps - 15fps (default: 15fps)
Sub stream: 10fps - 15fps (default: 15fps)		
Code Rate	Main stream: 1024Kbps - 4096Kbps (default: 3072Kbps)	
	Sub stream: 64Kbps - 672Kbps (default: 672Kbps)	
Audio	Two-way audio	
Power Requirements	Battery	28Wh rechargeable battery (Battery life varies based on settings, usage & temperature.)
	Solar	Reolink Solar Panel 2 (6W)
Interface	Power Port	USB Type-C port
	SD Card Slot	Supports Max. 128GB microSD card
	SIM Card Slot	Nano
	Reset Button	YES
	Audio In/Out	Built-in microphone and speaker
3G/4G	Frequency Bands	<ul style="list-style-type: none"> • Europe: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 • America: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 • Australia: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8
Software	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
	User Access	Max. 12 simultaneous streams (2 main & 10 sub streams)
Other Features	Smart Alarm	PIR detection; person detection; vehicle detection; animal detection
	PIR Detecting Distance	Adjustable up to 10m (33ft)
	PIR Detecting Angle	120° horizontal
	Recording Modes	Triggered recording
	Time Lapse	YES
	Smart Home Compatibility	Google Assistant; Alxea
Cloud Storage	Supports Reolink Cloud (available in selected countries)	
Working Environment	Operating Temperature	-10°C~+55°C (14°F~131°F)
	Operating Humidity	20% ~ 85%
	Weatherproof	IP65
Mechanical	Dimensions	Φ75 x 194mm
	Weight (Battery Included)	450g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us